



Features: R-410A REFRIGERANT

- High Efficiency Inverter
- Cooling Only
- Turbo mode
- Sleep Mode
- Auto Swing (Vertical Auto Swing)
- Auto Fan
- I Feel technology
- Dry Anti-Mildew Design
- Several Optional Filters
- Timer
- Auto Restart
- Dehumidify function
- Self Diagnosis
- LED
- Energy Saving
- Automatic Operation

TECHNICAL SPECIFICATIONS					
Indoor Unit Model		CG43MX009PH3H1C	CG43MX012PH3H1C	CG43MX018PH3H1C	CG43MX024PH3H1C
Outdoor Unit Model (includes piping kit)		CH43MX009-H3H1C	CH43MX012-H3H1C	CH43MX018-H3H1C	CH43MX024-H3H1C
Power Supply		208/230 V / 1Ph/60 Hz	208/230 V / 1Ph/60 Hz	208/230 V / 1Ph/60 Hz	208/230 V / 1Ph/60 Hz
Nominal cooling capacity (range)	BTU/h	9000 (3100 ~ 9600)	12000 (3100 ~ 13000)	18000 (6800 ~ 20000)	24000 (6800 ~ 29700)
Rated cooling capacity	BTU/h	9000	12000	18000	22000
Cooling input	W	630	923	1380	1650
Cooling current	A	2.8	4.5	6.1	7.2
SEER		23	22	20	20
Air flow volume	CFM (H/M/L/SL)	377/288/241/171	400/288/241/171	559/488/412/335	706/647/588/530
Indoor Unit					
Dimension (W*H*D) in inches		33.3×11.4×8.2	33.3×11.4×8.2	38.2×11.8×8.8	42.4×12.8×9.7
Dimension of carton box (W*H*D) in inches		36.1×10.9×14.3	36.1×10.9×14.3	40.9×14.9×12	45.1×16×13.2
Net weight (Lb)		22	22	27.5	34.2
Sound power level (dB(A))		53/49/45/39	55/49/45/39	57/53/50/49	58/54/50/46
Outdoor Unit					
Dimension (W*H*D) in inches		33.4×21.3×12.6	33.4×21.3×12.6	37.6×27.6×15.6	38.6×31.1×16.8
Dimension of carton box (W*H*D) in inches		34.6×14.2×22.8	34.6×14.2×24.8	40.4×17.9×28.9	42.5×19.1×33.1
Net weight (Lb)		73	80	103	148
Sound power level (dB(A))		63	64	65	69
Connection pipe	Liquid side/Gas side (inches)	1/4" / 3/8"	1/4" / 3/8"	1/4" / 1/2"	1/4" / 5/8"
Shipping per STD40HQ		300	300	284	284



Carrier InterAmerica Corporation
Miami, Florida USA
www.ciac-comfort.com

Authorized Dealer: